


# H05RR-F 橡胶电缆

H05RR-F rubber cable

阻燃 (Antiflaming) RoHS

产品图示 (Product icons)




## 1. 产品应用 APPLICATION:

这种电缆适合作为电气连接线用于各种家用电器，如：吸尘器，电熨斗等家庭或办公室中承受中等应力手持设备的场合，还适合固定在隔墙，装饰层及预制建筑部件中空空间等场合，适用于潮湿或干燥的室内，还适合室外长期使用，

The cable is suitable for the electric cable used in all kinds of household electrical appliances, Such as: Vacuum cleaners, electric iron, etc in the home or office under medium stress handheld devices, Also suitable for fixed installation in the partition, Adornment layer and precast hollow space building components, Apply to wet or dry room, Suitable for outdoor use for a long time,

## 2. 产品说明 PRODUCT DESCRIPTION:

性能参数 (performance parameter)	结构说明 (structure specification)
型号 (TYPE): H05 RR-F	导体: VDE 5类导体, 多股细软 (镀锡) 裸铜丝绞合
技术标准 (standards) 符合DIN VDE 0282; HD 22.4	conductor: multistrand fine conductor, conform VDE
额定电压 (Rated Voltage): 300/500V	绝缘: 线芯E14橡胶绝缘, 符合VDE 0282规定
使用温度 (Use Temperature) -30°C 至 +60°C	Insulation: E14 rubber insulation conform VDE 0282
最小弯曲半径 (Bend Radius)  8×产品外径 (Outer Diameter)	成缆: 绝缘芯线采用最优节距绞合成缆 线芯分色按VDE 0293规定
G: 有黄-绿接地线 ×: 无黄-绿接地线	cabling: core of cable adopt optimal pitch cabling cording to provisions of VDE 0293 color separation
	外护套: 外护套EM3橡胶被覆, 符合VDE 0282标准之规定
	Outer sheath: E3 rubber Outer sheath. conform VDE 0282

导体规格mm <sup>2</sup>	导体规格mm <sup>2</sup>
0.75	2 ~ 5 (芯)
1.0	2 ~ 5 (芯)
1.5	2 ~ 5 (芯)
2.5	2 ~ 5 (芯)
4.0	2 ~ 5 (芯)
6.0	2 ~ 5 (芯)
-	-

\* 其它规格可按客户需求订制




# H05RN-F 橡胶电缆

H05RN-F rubber cable

阻燃 (Antiflaming) RoHS

产品图示 (Product icons)




## 1. 产品应用 APPLICATION:

这种电缆适合作为电气连接线用于各种家用电器，如：吸尘器，电熨斗等家庭或办公室中承受中等应力手持设备的场合，还适合固定安装在隔墙，装饰层及预制建筑部件中空空间等场合，适用于潮湿或干燥的室内，还适合室外长期使用，可接触油脂和油。

The cable is suitable for the electric cable used in all kinds of household electrical appliances, Such as: Vacuum cleaners, electric iron, etc in the home or office under medium stress handheld devices, Also suitable for fixed installation in the partition, Adornment layer and precast hollow space building components, Apply to wet or dry room, Suitable for outdoor use for a long time, Can contact with grease and oil.

## 2. 产品说明 PRODUCT DESCRIPTION:

性能参数 (performance parameter)	结构说明 (structure specification)
型号 (TYPE): H05 RN-F	导体: VDE 5类导体, 多股细软 (镀锡) 裸铜丝绞合
技术标准 (standards) 符合DIN VDE 0282; HD 22.4	conductor: multistrand fine conductor, conform VDE
额定电压 (Rated Voltage): 300/500V	绝缘: 线芯E14橡胶绝缘, 符合VDE 0282规定
使用温度 (Use Temperature) -30°C 至 +60°C	Insulation: E14 rubber insulation conform VDE 0282
最小弯曲半径 (Bend Radius)  8×产品外径 (Outer Diameter)	成缆: 绝缘芯线采用最优节距绞合成缆 线芯分色按VDE 0293规定
G: 有黄-绿接地线 ×: 无黄-绿接地线	cabbling: core of cable adopt optimal pitch cabling cording to provisions of VDE 0293 color separation
	外护套: 外护套EM2橡胶被覆, 符合VDE 0282标准之规定
	Outer sheath: E2 rubber Outer sheath. conform VDE 0282

导体规格mm<sup>2</sup>

0.75

1.0

1.5

2.5

4.0

-

-

导体规格mm<sup>2</sup>

2 ~ 5 (芯)

2 ~ 5 (芯)

2 ~ 5 (芯)

2 ~ 5 (芯)

2 ~ 5 (芯)

-

-


\* 其它规格可按客户需求订制

# H07RN-F 橡胶电缆

H07RN-F rubber cable

阻燃 (Antiflaming) RoHS

产品图示 (Product icons)




## 1. 产品应用 APPLICATION:

这种电缆可做为连接电力工具, 机械设备和有中等机械应力要求的电缆, 可用于干燥或潮湿的室内, 也可在户外露天使用, 可以直接敷设在机器中, 如电梯和起重机, 可用于管道的设备中防护和固定安装,

This kind of cable can be connected as power tools, Machinery and equipment and there is a requirement for medium mechanical stress cable, Can be used for the dry or wet indoor, Also can be used in outdoor, may Direct installation In the machine, Such as elevator and crane, can be used for equipment protection and fixed in the installation of pipes

## 2. 产品说明 PRODUCT DESCRIPTION:

性能参数 (performance parameter)	结构说明 (structure specification)
型号 (TYPE): H07 RN-F	导体: VDE 5类导体, 多股细软 (镀锡) 裸铜丝绞合 conductor: multistrand fine conductor, conform VDE
技术标准 (standards) 符合DIN VDE 0282; HD 22.4	绝缘: 线芯E14橡胶绝缘, 符合VDE 0282规定 Insulation: E14 rubber insulation conform VDE 0282
额定电压 (Rated Voltage): 450/750V	成缆: 绝缘芯线采用最优节距绞合成缆 线芯分色按VDE 0293规定
使用温度 (Use Temperature) -30°C 至 +60°C	成缆: core of cable adopt optimal pitch cabling cording to provisions of VDE 0293 color separati
最小弯曲半径 (Bend Radius)  8×产品外径 (Outer Diameter)	外护套: 外护套EM2橡胶被覆, 符合VDE 0282标准之规定 Outer sheath: E2 rubber Outer sheath. conform VDE 0282
G: 有黄-绿接地线 ×: 无黄-绿接地线	

导体规格mm <sup>2</sup>	导体规格mm <sup>2</sup>
1×1.5	2 ~ 5 (芯)
1×2.5	2 ~ 5 (芯)
1×4	2 ~ 5 (芯)
1×6	2 ~ 5 (芯)
1G1.5	2 ~ 5 (芯)
1G2.5	2 ~ 5 (芯)
1G4	2 ~ 5 (芯)
1G6	2 ~ 5 (芯)

\* 其它规格可按客户需求订制




# H01N2-D/-E 电焊机专用电缆

H01N2-D/-E Electric welding machine dedicated cable

阻燃 (Antiflaming) RoHS

产品图示 (Product icons)



## 1. 产品应用 APPLICATION:

这种电缆是专用于电焊机到焊枪的大电流输送而特别设计的, 适合恶劣环境下有柔性要求的场合, 也可用于装配线, 运输, 机床, 汽车工业和电焊机的安装连接, 即使在强光, 臭氧, 氧气, 惰性气体, 油脂侵蚀时, 电缆仍可以保持高柔性, 同时还耐寒, 耐热, 阻燃等, 这种电缆适用于干燥和潮湿的室内, 也可以露天使用。

This cable is dedicated to electric welding machine specially designed to torch high current conveyor, Suitable for harsh environments have flexible requirements, Can also be used for the assembly line, transport, machine tools, automobile industry and the installation of the welding machine connection, Even in bright light, ozone, oxygen and inert gas, oil and grease erosion, Cable can still maintain a high flexible, At the same time also to cold, heat resistant, flame retardant, etc; This cable is suitable for the dry and wet indoor, Also can be used in outdoor.

## 2. 产品说明 PRODUCT DESCRIPTION:

性能参数 (performance parameter)		结构说明 (structure specification)	
型号 (TYPE):	H01N2-D/-D H01N2-D/-E	导体:	H01N2-E VDE 6类导体多股绞合 H01N2-D 精细铜丝多股绞合
技术标准 (standards)	符合DIN VDE 0282-6; HD 22.6	Conductor:	H01N2-E: VDE 6Type of conductor H01N2-D : multistrand Fine copper wire
额定电压 (Rated Voltage):	100V	绝缘:	导体绞合后包覆隔离层 黑色氯丁橡胶外护套
使用温度 Use Temperature		Insulation:	Stranded conductor coated after isolation layer Black neoprene outer sheath
挠曲 bend	-20℃ 至 +70℃	试验交流电压	50Hz 1000V
静态 static state	-40℃ 至 +80℃	The test voltage	
最小弯曲半径 (Bend Radius)	10×产品外径 (OuterDiameter ) 12×产品外径 (OuterDiameter )	耐油试验	按照VDE 0472第803部份A类试验
		oil resistant test	According to VDE 0472 803th part of the class A test
		耐燃烧试验	按照VDE 0472第804部份B类试验
		flame resistance	According to VDE 0472 804th part of the class B test

H01N2-D	H01N2-E
1×10	1×10
1×16	1×16
1×25	1×25
1×35	1×35
1×50	1×50
1×70	1×70
1×95	1×95

\* 其它规格可按客户需求订制

